

Model Number


V3-WM-20M-PVC

Female cordset, M8, 3-pin, PVC cable

Features

- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Gold plated contacts


Dimensions



Technical data

General specifications		
Number of pins		3
Electrical specifications		
Operating voltage	U_B	max. 60 V DC
Test voltage		> 1500 V_{eff} AC
Operating current	I_B	max. 4 A
Volume resistance		< 5 mΩ
Ambient conditions		
Ambient temperature		-25 ... 100 °C (-13 ... 212 °F) for temperatures over 80 °C (176 °F) reduced elongation at tear
Pollution degree		3
Mechanical specifications		
Contact elements		spring-loaded contact socket
Pin diameter		1 mm
Degree of protection		IP67
Material		
Contacts		CuSn / Au
Contact surface		Au
Body		TPU, black
Cable		PVC
Slotted nut		Diecast zinc
Core insolation		PVC
Cable		fine-strand, flexible
Sheath diameter		Ø4.8 mm
Bending radius		> 10 x cable diameter, moving
Color		grey
Number of cores		3
Core cross-section		0.34 mm^2
Length	L	20 m
Flammability		
Contact carrier		94 V-2
Housing		94 V-2

Electrical connection



Release date: 2016-03-15 16:00 Date of issue: 2016-03-15 231394_eng.xml